

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: Emzone Non-Chlor. Brake & Parts Cleaner/Pull up spout- 18.9L CODE: 044140

Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identity..... Emzone Non-Chlor. Brake & Parts Cleaner/Pull up spout- 18.9L

Product Item Numbers..... 044140

Manufactured by..... Empack Spraytech Inc.

98 Walker Drive Brampton

Ontario Canada L6T 4H6 905-792-6571

24 hour emergency telephone number....... CANUTEC: (613)-996-6666 collect.

Recommended Use..... Cleaning solvent.

Consumer Commodity.....

Hazard Ratings:

HMIS..... NFPA Rating.....

Health: 1 Fire: 3 Reactivity: 0 PPE: G. Health: 1 Fire: 3 Reactivity: 0 Special: - .

Section 02: HAZARDS IDENTIFICATION

Emergency Overview..... Highly flammable liquid and vapour. May be fatal if swallowed and enters airways

Aspiration hazard. Causes skin irritation. May cause drowsiness or dizziness. KEEP OUT

OF REACH OF CHILDREN.

Potential Health Effects:

Eye Contact.....

Skin Contact.....

Ingestion..... Inhalation..... This product causes irritation, redness and pain.

Can cause skin irritation. Prolonged or repeated contact may dry the skin.

May be fatal if swallowed.

Inhalation may cause respiratory tract irritation. Can cause Central Nervous System (CNS)

depression; symptoms include nausea, headache, dizziness, unconsciousness.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

CAS# Hazardous Ingredients Wt. %

142-82-5 60-100 Heptane

Section 04: FIRST AID MEASURES

Check for and remove contact lenses. Immediately flush eyes with water for a minimum of Eye Contact.....

15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms Skin Contact..... persist, seek medical attention.

Call a physician or Poison Control Centre immediately. Keep respiratory tract clear. Never Ingestion.....

give anything by mouth to an unconscious person. Inhalation.....

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical

attention.

Note to the doctor; treat symptomatically. Contains material that is an aspiration hazard. Additional Information.....

Potential danger from aspiration must be weighed against possible oral toxicity when

deciding whether to induce vomiting.

Section 05: FIRE FIGHTING MEASURES

Flammability Class..... Extremely Flammable.

Small Fire: Use Dry Chemical. Large Fire: Use water spray or fog. Extinguishing Media.....

Sensitivity to Mechanical Impact..... Not expected to be sensitive. Sensitivity to Static Discharge.....

Not expected to be sensitive.

Section 06: ACCIDENTAL RELEASE MEASURES

Spills and Leaks.....

Put on appropriate personal protective equipment (see Section 08). Eliminate all sources of ignition and ventilate area. Contain spillage, and then collect with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13). CAUTION: Leak/spill may cause slippery surface.

PRODUCT: Emzone Non-Chlor. Brake & Parts Cleaner/Pull up spout- 18.9L CODE: 044140

Section 07: HANDLING AND STORAGE

ventilation. For personal protection see Section 08. Ground all equipment containing the material. Wash skin thoroughly after handling. Keep away from heat and sparks. Keep away from sources of ignition. Do not smoke while handling the product. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked-up.

Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/Type...... Safety glasses with side-shields.

for mists and vapours.

conditions. Use local exhaust ventilation to maintain airborne levels below the Threshold

for a ceiling conc.

Limit Value.

Exposure Limits

Toxicological Data

Ingredients	TWA	SIH TLV STEL	OSH. PEL	A PEL STEL	NIOSH REL
Heptane	400 ppm	500 ppm	500 ppm	Not available	85 ppm for n-Heptane, 440 ppm

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid.
Physical Appearance	Clear liquid.
Odour	Hydrocarbons.
Odour Threshold (ppm)	Not available.
pH	Not applicable.
Vapour Pressure (psig)	Not available.
Vapour Density (Air=1)	Not available.
Evaporation Rate (n-Butyl Acetate = 1)	>1.
Initial Boiling Point/Boiling Range (°C)	98 °C (209°F).
VOC Content	95-100 %wt.
Specific Gravity (liquid)	0.660-0.690.
Specific Gravity (Aerosol)	Not applicable.
Solubility in water	Negligible.
Aerosol Flame Projection	Not applicable.
Auto Ignition Temperature (°C)	204°C (399°F).
Flashback	Yes.
Flash Point (°C), Method	 4 °C / 24.8 °F (Closed Cup).
Lower Flammable Limit (% Vol)	1.1.
Upper Flammable Limit (% Vol)	6.7.

Section 10: STABILITY AND REACTIVITY

Stability...... Stable at normal temperatures and pressures.

Incompatibility...... Strong oxidizing agents.

Conditions to Avoid....... Avoid sources of heat and flame, and electrostatic charge.

Hazardous Products of Decomposition....... May form carbon dioxide and carbon monoxide, various hydrocarbons.

Hazardous Polymerization...... Will not occur.

Section 11: TOXICOLOGICAL INFORMATION

	CALLIT DATA OFFICE	i age e	
PRODUCT: Emzone Non-Chlor. Br	rake & Parts Cleaner/Pull up spou	t- 18.9L CODE: 044140	
Section 11	1: TOXICOLOGICAL INFORMATIO	N	
Ingredients LC5	50	LD50	
Heptane 103,	000 mg/L (4hrs - rat)	>15,000 mg/kg (rat - oral); >2,000 mg/kg (rabbit - dermal)	
Section	12: ECOLOGICAL INFORMATION		
Environmental	Very toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Heptane: Toxicity to fish: LC50 1.284 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 0.1 mg/L, 96 hrs; Toxicity to algae: EL50 4.338 mg/L, 72 hrs.		
Section 1	3: DISPOSAL CONSIDERATIONS		
Appropriate Disposal Methods	Dispose in accordance with local, provincial and federal regulations.		
Section	14: TRANSPORT INFORMATION		
TDG (Canada- Road) DOT (US-Road) IMDG (International- Marine) IATA (International- Air)	HEPTANES, Class 3, UN1206. HEPTANES, Class 3, UN1206.		
Section	15: REGULATORY INFORMATION		
CanadaUSA	WHMIS Classification. B2: Flammable liquid. D2B: Material causing other toxic Materials. Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200).		
Section	on 16: OTHER INFORMATION		
Disclaimer	The information contained herin is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the		
Abbreviations	CPR. THIS SDS IS VALID FOR THREE Y ACGIH: American Conference of Governn Abstract Service; NIOSH: National Institut Occupational Safety and Health Administr 1976-USA; PEL: Permissible Exposure Lir	EARS. nental Industrial Hygienists; CAS: Chemical e for Occupational Safety and Health, OSHA: ation- USA; TSCA: Toxic Substances Control Act mit; REL: Recommended Exposure Limit; TLV: inic Content; WHIMIS: Workplace Hazardous	
Prepared byPreparation DateLast Revision Date	Regulatory Affairs Sep30/13		